Details zur Standtrennwand

250 cm Höhe

Bitte beachten Sie, dass die Standwände nur aufgebaut werden, wenn Sie dies explizit wünschen und/oder im Shop für Ausstellerservices bestellen. Sofern Ihr Standnachbar Standtrennwände wünscht, werden diese ebenfalls aufgestellt.
Die Standtrennwände sind rein funktional und keine dekorativen Showwände.

Maße	Wandelemente inkl. Kabelkanal Höhe: **250 cm**, Breite:100 oder 50cm, Tiefe: 4 cm Gesamthöhe, inklusive Verstellfüße, Oberkante bei ca. **260 cm**
Beschaffenheit Eigenschaften	Jedes Wandelement besteht aus einer Wabenkonstruktion als Mittellage, mit Spanplatte verkleidet, folienbeschichtet und weiß lackiert. Die Oberkante ist mit einem Kabelkanal versehen. Es sind jeweils 2 Verstellfüße zum Ausgleich der Bodenunebenheiten integriert. Die Wände dürfen nicht durch Nageln, Schrauben, Streichen, Bekleben oder Ähnliches beschädigt werden. Kaschierungen müssen vom Verursacher nach der Messe rückstandfrei entfernt werden. Die Wandelemente sind in den Breiten 100 cm und 50 cm verfügbar. Die Abgänge/Anschlüsse der Wände sind im Winkel von 90 Grad möglich. Ab 5 m sind auf Ihrer Standfläche Stützwände im 90-Grad-Winkel von 100 cm Tiefe erforderlich. Platzierungswünsche der Stützwände sind nach Absprache möglich. Die maximale Belastung pro Wandelement ist 20 kg. Bei einer Belastung ab 30kg über mehrere Wandelemente wenden Sie sich bitte an den technischen Ansprechpartner. Um die Lücke (ca. 10 cm), die aufgrund der Verstellfüße entsteht, zu verdecken, wird die Anbringung von Sockelleisten empfohlen.
Tapezieren und Streichen	Die Wände befinden sich in einem technisch einwandfreien Zustand und sind mit einer standardmäßigen weißen Grundlackierung versehen. Wenn Sie Ihre Wände in einer anderen Farbe als in weiß gestrichen haben möchten, müssen aus Materialschutzgründen die Wände vorher tapeziert werden. Mit einer Tapeziergenehmigung können Sie die Arbeiten mit eigener Tapete und Farbe selbst durchführen oder Sie können alle Arbeiten durch uns durchführen lassen.
Gestaltungsmöglichkeiten	Diese und weitere Optionen zur Gestaltung der Standtrennwände, wie das Anbringen von Sockelleisten oder Blenden, finden Sie in unserem Shop für Ausstellerservices über den Link: serviceshop.messefrankfurt.com.
Kontakt	**Messe Frankfurt Medien und Service GmbH** **Fairconstruction** Ludwig-Erhard-Anlage 1 60327 Frankfurt am Main Telefon: +49 69 75 75-66 66 E-Mail: walls.fairconstruction@messefrankfurt.com

Details on Stand Dividing Wall

250 cm Height

Please note that the stand dividing walls will only be set up if you specifically request them and/or order them in the shop for exhibitor services. If your stand neighbor requests the stand dividing walls, the walls facing your stand space will also be set up. **The stand dividing walls are purely functional and are not decorative show walls.**

Dimensions	Wall element incl. cable channel: Height: **250 cm**, Width: 100 or 50 cm, Depth: 4 cm Total height, including adjustable feet, top edge at approx. **260 cm**
Description Characteristics	Each wall element consists of a honeycomb structure in the middle layer, covered with chipboard, foil-coated and sprayed white. The top edge is equipped with a cable channel. Two adjustable feet are built in to compensate for uneven floors. The walls must not be damaged by nailing, screwing, painting, sticking or similar actions. Any attachments must be removed by the user after the trade show without leaving any residue. The wall panels are available in widths of 100 cm and 50 cm. The walls can be joined at a 90-degree angle. For lengths of 5 m or more, support walls with a depth of 100 cm and positioned at a 90-degree angle are required within your stand space. Requests regarding the placement of the support walls can be discussed. The maximum load per wall panel is 20 kg. For loads of 30 kg or more distributed across multiple wall panels, please contact the technical representative. To cover the gap (approx. 10 cm) created by the adjustable feet, we recommend installing skirting boards.
Wallpapering and Painting	The walls are in perfect technical condition and have a standard white base coat. If you would like your walls painted in a different color than white, they must be wallpapered first to protect the material. With a wallpapering permit, you can carry out the work yourself using your own wallpaper and paint, or you can have us carry out all the work.
Design Options	You can find these and other options for customizing the stand dividing walls, such as installing skirting boards or fascia boards, in our Exhibitor Services Shop via the link: serviceshop.messefrankfurt.com.
Contact	**Messe Frankfurt Medien und Service GmbH** **Fairconstruction** Ludwig-Erhard-Anlage 1 60327 Frankfurt am Main Phone number: +49 69 75 75-66 66 E-Mail: walls.fairconstruction@messefrankfurt.com

fairconstruction









